

Premium  
Quality



# Bristo™

## CEMENT PRIMER Interior & Exterior



Quick drying

Better sealing

Alkali resistant

High performance

Superior Whiteness & Brightness



**KWALITY WALLCOATINGS PVT. LTD.**



# Bristo™

**SURYA BRISTO CEMENT PRIMER** is water based, premium quality primer Manufactures using highly graded micron extenders and Acrylic Emulsion to give an ultimate bonding over Concrete, Masonry surfaces, Pebble dash, Asbestos surface and Brick Masonry works, before application of any Water Based Acrylic Paints. it is also recommended over any putty, both Acrylic and Cement based putties, before applying Emulsion Paints.

### **SURFACE PREPARATION :**

All surfaces should be completely dry and free from oil and grese etc. Oid painted surfaces should be cleaned by scrapping or by using a good paint remover and then clening the surface with water and madedry. If the surface is rough, it should be made even by abrading it using suitable emery paper or wire brush and clean to make it free from dust particles.

### **METHOD OF APPLICATION :**

**SURYA BRISTO CEMENT PRIMER** should be thoroughly mixed in a clen vessel with water in the ratio of one part of primer with 0.4 - 0.5 parts of clean water. Apply this mix on the desired surface with a good brush/roller evenly and finishit with the same. Allow the surface to dry at least for a period of 3 - 4 hours applying any Emulsion paint. This drying period may slightly vary depending upon the ambient temperature; hence ensure that the primed surface is completely dry before application with paint.

Over this primed surface apply the desired Acrylic Emulsion paint, as per requirement.

### **COVERAGE :**

One litre of **SURYA BRISTO CEMENT PRIMER** will cover approximately 100 to 120 sq.ft and this may vary depending on the surface.

### **PRECAUTION :**

Store **SURYA BRISTO CEMENT PRIMER** is original containers in a cool dry place Any leftover mixed primer at the end of the day's work should not be mixed with fresh primer as it will lead to spoiling of the mate ial due to microbiological contamination. Such leftover mix should br used immediately the next day or should be discarded. Use good quality water for mixing with primer to prevent any contamination. Wash hands with soap and water at the end of the day's work. in case of eye contact wash with water and obtain medical attention.

### **PACKING :**

1 Ltr, and 4 ltrs in containers,  
10 ltrs and 20 ltrs in pails.



Manufactured & Marketed by:

**KWALITY WALLCOATINGS PVT. LTD.**

#19-897, Guntur Road, Piduguralla-522413, Guntur Dist.  
Andhra Pradesh | E-mail: [kwalitywallcoatings@gmail.com](mailto:kwalitywallcoatings@gmail.com)